

SPECIAL PRODUCTS

MAKE YOUR PRODUCTION EASY



Flexibility

Super flexibility of the base permits its using in all types of PVC and ALU profiles

Packaging

Revolutionary packaging on reels

Easy transport

Easy transport and storage on euro pallets

Automatic insertion

Made for automatic insertion due to exhaustive and repetitive tolerances

Infinity combinations

Infinity combinations between monofilament, yarn and fins in one item

Rigidity

Different grade of rigidity depending of its use



Easy cutting

Easy cutting – with regular scissors (you can use the product until the last centimetres)

CSF/SRF/SRF D100-D200

Examples of Applications:

- garage doors
- industrial doors
- door bottoms
- roller-shutter boxes
- cable guides or cable ways on furniture or electrical cabinets
- sun awnings systems (clean an awning covers)
- conveyor belt seals/guides
- folding and sliding doors systems



SPECIAL PRODUCTS

MAKE YOUR PRODUCTION EASY



REFORCED PILE WEATHERSTRIPPING SRF HIGH DENSITY FLEXIBLE INDUSTRIAL BRUSH WITH FIN CSF


CARACTERISTICS

Pile/monofilament heights: from 4mm to 35mm
Insitey pile/monofilament + multifilament:
 from 2P1M to 2P8M
 (monofilament can be inside and
 outside of the pile)
Standard base widths: from 4mm to 9mm
Yarn colours: black, grey, white


Monofilament colours: black and transparent
Density only monofilament:
 D50, D100, D150, D200
Fin materials: plastic fin and quiet fin
Fin colours: black, grey and transparent

TOLERANCES

Base width: +0.1mm -0.2mm
Pile/monofilament height: +0.25mm -0.15mm
Base thickness: 0.74mm ±0.1mm
Pile width: 1.5mm ±0.15mm
Fin heights: CSF ±0.2mm, HSF ±0.5mm



SRF



CSF


HIGH DENSITY FLEXIBLE INDUSTRIAL BRUSH SRF D200

CARACTERISTICS

Pile/monofilament heights: from 4mm to 35mm
Density only monofilament: D50, D100, D150, D200
Standard base widths: from 4mm to 9mm
Monofilament colours: black and transparent

TOLERANCES

Base width: +0.1mm -0.2mm
Pile/monofilament height: +0.25mm -0.15mm
Base thickness: 0.74mm ±0.1mm
Pile width: 1.5mm ±0.15mm



SRF D200



PACKAGING SRF AND SRF D200

Base width from 4.8mm to 9mm		
Height [mm]	Reel [m]	Box [m]
4	700	1400
5	650	1300
6	600	1200
7	550	1100
8	500	1000
9	450	900
10	400	800
11	350	700
12	300	600
13	300	600
14	250	500
15	250	500
16	200	400
17	200	400
18	200	400
19	175	350
20	175	350
22	125	250
24	100	200
26	100	200

PACKAGING CSF

Base width from 4.8mm to 9mm		
Height [mm]	Reel [m]	Box [m]
4	650	1300
5	600	1200
6	550	1100
7	500	1000
8	450	900
9	400	800
10	350	700
11	325	650
12	275	550
13	275	550
14	250	500
15	250	500
16	200	400
17	200	400
18	200	400
19	175	350
20	175	350
22	125	250
24	100	250
26	100	250